

# SINGLE CLAMP PERFECT BINDING MACHINE



## SILENT FEATURE

- Single clamp perfect binder with easily adjustable book clamp.
- Milling station with the cutter, notching teeth, and a powerful dust extractor
- Gluing-various options available (see technical data below)
- Cover the nipping station with the facility to control the nipping pressure.
- Timers for adjusting feed-in time, cover nipping duration, and delivery.
- A wide range of jobs can be done with easy job changeover.
- Excellent productivity
- High-quality bookbinding
- Quick change over
- Easily adjustable book clamp
- Side gluing rollers for an even layer
- Top up a production facility
- Book counter system incorporated
- No requirement of skill operator
- Controlled labor costs
- Optional strip-type milling cutter (up to 40mm spine thickness) which removes paper from the book spine in strips

## TECHNICAL SPECIFICATION

Min.spine length	50mm
Max.spine length	435mm
Min.page width	50mm
Max.page width	300mm
Bindable thickness	1-50mm
Speed p/h	700books
2 up production	1250books
Power requirement	410/440v
Motor HP	4
Heater	2kw
Machine size	2275 X 645 mm
Machine weight (Approx)	850 kgs
Adhesive	Hot melt

Reg. Office

**NATIONAL INDUSTRIES**

R-13, Ansal Chamber-1, Ground Floor, Bhikaji Cama place  
New Delhi-110066 (INDIA), Opp. Bhikaji Cama Place Metro Station  
Phone: 9555086767, 9312286767, 8130966224

Customer Care: 1800-3010-7005 | Email: sales@namibind.com | www.namibind.com

